



TransferRite® 1510, 1520 Clear

PRODUCT DESCRIPTION

A unique clear polypropylene film backing with a custom formulated latex P/S adhesive for decal transfer and pre-spacing.

Used where precise registration is required and designed to assist in the application of P/S decals that have been cut into letters and legends.

PRODUCT SPECIFICATIONS

	1510	1520
Typical Uses	<ul style="list-style-type: none">• Pre-spaced lettering 2"-12" high• Decals or lettering <12" in one dimension• Fine line striping	<ul style="list-style-type: none">• Pre-spaced lettering <12" high• Heavily weeded, thermal die cut decals
Total thickness	4.6 mils	4.8 mils
Adhesion to Steel PSTC-101 (180°, oz./in.)	9 (Medium)	19 (high)
Tensile strength PSTC-31	18 lbs/inch	18 lbs/inch
Elongation PSTC-31	600%	600%

The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for their intended use under their own operating conditions. Protective Packaging assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.